

Enable optical port on H3C switch

The following uses the Moduletek QSFP-40G-LR4 module connected to an H3C S6820 switch as an example to introduce how to read information of the connected optical module on an ...

Consider the site ventilation design when you plan the installation site for the switch. The switch uses removable fan trays. It provides airflow from the port side to the power supply side or from power ...

Enable the 802.1X feature of the port Add local access users and set related parameters View 802.1X information Link Aggregation Configuration ...

You can specify a Combo port to operate as an electrical port or an optical port. That is, a Combo port cannot operate as both an electrical port and an optical port simultaneously.

H3C switch configuration description: Due to the use of port parameters, the port will be taken as a reference, that is, at this time, port E0 / 1 only allows PC1 to access the Internet, while PCs using ...

You can install a transceiver module (see "Installing a QSFP+/QSFP28 transceiver module") in a fiber port and use an optical fiber to connect the port to the network.

Loop detection--When the system detects a loop on a port, it does not take any actions on the port, but it will display a red icon for the port on the port state pane.

The authentication port (UDP) used by RADIUS servers is 1812 according to standard RADIUS protocols. However, the port (UDP) is set to 1645 on an H3C device that functions as the ...

Whether you're a network administrator or just starting out with networking, this video will provide you with the knowledge to confidently configure your H3C switch.

Enable the 802.1X feature of the port Add local access users and set related parameters View 802.1X information Link Aggregation Configuration Create an aggregation port Add Ethernet ...

H3C switch configuration description: Due to the use of port parameters, the port will be taken as a reference, that is, at this time, port E0 / 1 only allows PC1 to access ...

The combo enable copper and combo enable fiber commands can be used to flexibly switch the working mode of an interface to meet networking requirements in different scenarios. This ...

Web: <https://tlaletsoglobal.co.za>